

Pluto Non DI_Asean

90x127mm

Control

Mode switch/
Filter reset
• Auto • Turbo • Sleep

Power on/off

Display

Air quality light

Air quality
Good Fair Poor Very poor

Filter replacement alert

Maintenance

Clean the surface of the filter

Replace filter when display shows

• Clean the surface of the filter every 4 weeks.

• Replace the NanoProtect Filter Series 2 (FY0194). Long press the for 3 seconds.

The filter may produce smell after being used for a while because of the absorption of indoor air. Remove the filter and place it where it has direct sunlight and ventilation for several hours. Re-install and try using it again. If the odor remains, please replace the filter.

3000 035 54621

控制

模式切換/
濾網重設
• 自動 • 特強 • 睡眠

電源開啟/關閉

顯示

空氣質素指示燈

空氣質素水平
良好 一般 差 非常差

濾網更換提示

維護

清潔濾網表面

顯示 時，更換濾網

• 每 4 週清潔濾網表面

• 更換濾網 (FY0194) 後，長按 3 秒。

開始使用後的濾網因吸收了室內空氣，可能會產生少許異味。取出過濾網並放置在陽光直射和通風的地方數小時。重新安裝過濾網，再次嘗試使用。如果仍有異味，請更換過濾網。